

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number  
**WO 03/088285 A1**

(51) International Patent Classification<sup>7</sup>: **H01F 27/28**

Dan [US/US]; 2378 North Sun Lake Place, Tucson, AZ 85711 (US). DAVILA, Marco, A. [US/US]; 4754 N. Coop Canyon Place, Tucson, AZ 85750 (US).

(21) International Application Number: PCT/CH03/00246

(22) International Filing Date: 11 April 2003 (11.04.2003)

(74) Agents: ROSHARDT, Werner, A. et al.; Keller & Partner Patentanwälte AG, Schmiedenplatz 5, Postfach, CH-3000 Bern 7 (CH).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated State (*national*): US.

(30) Priority Data:  
60/372,279 12 April 2002 (12.04.2002) US

(84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(71) Applicant (*for all designated States except US*): ASCOM ENERGY SYSTEMS AG [CH/CH]; Belpstrasse 37, CH-3000 Bern 14 (CH).


Published:  
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): JITARU, Ionel,

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: LOW PROFILE MAGNETIC ELEMENT



(57) **Abstract:** A low profile magnetic element used in cooperation with a multilayer printed circuit board has two or more core arms penetrating the board from one outer surface to the other and a series of magnetic core elements, at least one on each side of the board, bridging pairs of the core arms to form a closed, unbranched flux path. Series-connected windings form a transformer primary and are wound on the core arms that penetrate the board. Parallel-connected windings form a transformer secondary and are also wound on the core arms. The series-connected windings and the parallel-connected windings may be buried windings printed on internal surfaces of the multilayer board. The connected in series primary windings all have the same number of turns and the parallel-connected secondary windings all have the same number of turns. The parallel secondary windings are connected in current additive fashion to afford a high current transformer output. Output treating circuitry can treat each output separately in parallel and identically, being connected between the winding outputs and their point of connection. The transformer core can be assembled entirely of C and I magnetic elements. In one embodiment, a pair of magnetic plates overlying the outer surfaces of the multilayer circuit board are in flux-conducting relation with all of the core arms penetrating the board.

WO 03/088285 A1